

LI-ION RECHARGEABLE

XPR-5580R

XPR-5580G

VIRIBUS™ INTRINSICALLY SAFE DUAL-LIGHT LANTERN

NIGHTSTICK®
Life Depends on Light™




Rear green safety lights provide visibility in smoke filled applications. Includes one Li-ion battery (expandable to 3).



Carry strap with seat belt style buckle for additional hands-free use and safety.



Convenient locking snap-in charger included.



Sealed switches and body for **dustproof/waterproof (IP-67)** rating, as well as chemical/heat resistant for any environment.

**DUAL
LIGHT
TECHNOLOGY**



AVAILABLE IN HI-VIZ GREEN.



**ATEX
ZONE 0
IECEx**

**CLASS I
DIV 1**

IT FLOATS



300 LUMENS

1-800-233-2155 • 1-469-326-9400 • nightstick.com

© 2023 Bayco Products Inc. Items shown are intended as a visual representation only and are subject to change without notice. Visit nightstick.com for product updates.

VIRIBUS™

DUAL-LIGHT LANTERN

LI-ION RECHARGEABLE

ITEM NUMBER/UPC

XPR-5580G, UPC# 017398805957
XPR-5580R, UPC# 017398805964

MARKET APPLICATIONS

Hazardous work environments, fire, rescue, industrial and automotive

CERTIFICATIONS

- cULus, ATEX, IECEx, CE, UKCA
- Meets requirements of NFPA-1971-8.6 (2016), Charger meets requirements of NFPA-1901 (2013) Mounted in any Position

CASE MATERIAL

- Engineered polymer

LUMENS/RUNTIME

FLASHLIGHT

- HIGH: 210L, 12.5 hrs. runtime
- MEDIUM: 100L, 19.5 hrs. runtime
- LOW: 30L, 65 hrs. runtime

FLOODLIGHT

- HIGH: 200L, 14 hrs. runtime
- MEDIUM: 100L, 19 hrs. runtime
- LOW: 30L, 65 hrs. runtime

DUAL-LIGHT

- 300L, 9.25 hrs. runtime

CANDELA

FLASHLIGHT

- HIGH: 101,000
- MEDIUM: 16,515
- LOW: 6,705

BEAM DISTANCE

FLASHLIGHT

- HIGH: 635m
- MEDIUM: 257m
- LOW: 164m

WATER RATING

- IP-67 (dustproof and waterproof)

DROP RATING

- 2 meters

DIMENSIONS

- LENGTH: 8.25 in (210mm)
- WIDTH: 3.6 in (91mm)
- DEPTH: 5.5 in (140mm)
- BEZEL DIAMETER: 4.7 in (118mm)
- WEIGHT: 2 lbs. 1oz. / 936 g

BATTERY

- Rechargeable Li-ion battery pack

WARRANTY

- Limited lifetime warranty

WHAT'S INCLUDED

- Lantern
- (1) Li-ion rechargeable battery (5500-BATT)
- Locking snap-in charger (5580-CHGR2)
- AC & DC power supply (NS-ACCORD & NS-DCCORD)
- Removable shoulder strap
- Instruction manual

FL1 STANDARD	FLASH HIGH	FLASH LOW	DUAL-LIGHT
	210 LUMENS	30 LUMENS	300 LUMENS
	12h	65h	9h 15min
	635m		
	101000cd		

Bayco Products, Inc. XPR-5580
Wylie, TX 75098

Ex ia FLASHLIGHT FOR USE IN HAZARDOUS LOCATIONS
UL listed for use with Bayco Li-ion Battery Pack 5500-BATT

CLASS I DIV 1 GRP A-D T4
CLASS II & III DIV 1 GRP E-G
CLASS I ZONE 0 GRP IIC T4
CLASS II ZONE 20 IIC T135°C
@ II 1 G Ex ia IIC T4 Ga

Ex ia IIC T4 Ga
DEMKO 16 ATEX 1796
UL22UK2K2427
IECEx UL 16.0154
-20°C ≤ Tamb ≤ +40°C
3.7V/Cell 5500-BATT
U_n = 4.75V

CE 2575 **UK CA** 0359

SEE INSTRUCTION MANUAL
VOIR MANUEL

MFG MM-YY

CERTIFIED									