

Sleeve Cover

- Resistant to liquid, oil and grease
- Extend arm protection area beyond the glove

Style No.	DD302
Fabric	Microporous Film Laminated PPSB
Seam Type	4-thread Overlocked Seam 7-9 stitches per inch - Thread fiber is 150D - Bite depth at 4 mm
Color	White
Size	Uni Size (Length:47 cm)
Packing	100 pairs/carton
Approvals	CE Regulation (EU) 2016/425 UKCA Regulation 2016/425 Module B Certification Module D Certification

Certifications



TYPE PB[6-B]



EN 14126

Applications



Biological Hazards



Disease Control



Pharmaceutical

Technical Data

PHYSICAL PROPERTIES	TEST METHOD	CLASS
Abrasion Resistance	EN ISO 12947-2	2
Flex Cracking Resistance	EN ISO 7854/B	6
Trapezoidal Tear Resist.	EN ISO 9073-4	2
Tensile Strength	EN ISO 13934-1	1
Puncture Resistance	EN 863	2
Seam Strength	EN ISO 13935-2	3
pH Value	EN ISO 3071	Pass
Resistance to Ignition	EN 13274-4	Pass
Moisture Vapor Transmission Rate (MVTR)	ASTM E96B	7,123 g/m ² *24hr
Water Vapor Resistance (Ret)	EN ISO 11092	21.0 Pa*m ² /W

CHEMICAL PROPERTIES	TEST METHOD	PENETRATION	REPELLENCY
Sulfuric Acid (30%)	EN ISO 6530	3	3
Sodium Hydroxide (10%)	EN ISO 6530	3	3
O-Xylene	EN ISO 6530	3	3
Butan-1-ol	EN ISO 6530	3	3

AGAINST INFECTIVE AGENTS	TEST METHOD	CLASS
Resistance to penetration by blood / fluids	ISO 16603:2004	6
Resistance to penetration by blood-borne pathogens	ISO 16604:2004	6
Resistance to wet microbial penetration	ISO 22610:2006	6
Resistance to liquid aerosol penetration	ISO/DIS 22611:2003	3
Resistance to dry microbial penetration	ISO 22612:2005	3

Limitations



Do not wash



Do not dry clean



Do not iron



Do not machine dry



Do not reuse



Keep away from fire

Storage & Disposal

- Store clean and in original packaging at 15°C to 25°C (58°F to 78°F) with <80% humidity
- Store away from sunlight, high temperatures, and solvents
- Shelf life is 60 months from manufacture if stored as above
- Handle and dispose of contaminated garments carefully according to national regulations