

2 CR123

XPP-5465R

INTRINSICALLY SAFE FORGE® HELMET LIGHT

NIGHTSTICK®
Life Depends on Light

NEW 360° MOUNT

Positions light **at any angle**
and **holds firm**.

MEETS

NFPA

1971-8.6 (2018)

REQUIREMENTS



Multi-function brightness settings
illuminate large, smoke-filled
fireground locations or **SCBA gauges**.

LED POWER


**200+ METER
BEAM DISTANCE**



Durable **integrated mount** clamps
light securely to nearly all helmets,
either above or below the brim.



360-degree mount provides user
infinite aiming options, as well as
clearance for external shields.



Helmet clamp features **no-mar
rubber foot** and included Allen
wrench for robust grip and peace
of mind.



Rear-facing green LED-illuminated
button is **designed to be
activated with gloved hand**.



360 LUMENS

1-800-233-2155 • 1-469-326-9400 • nightstick.com

© 2019 Bayco Products Inc. Items shown are intended as a visual representation for informational purposes only and are subject to change without notice. Visit nightstick.com for product updates.

FORGE[®]

HELMET LIGHT

2 CR123

ITEM NUMBER/UPC

XPP-5465R - 017398807135

CERTIFICATIONS

- CE
- cETLus
- Meets the requirements of NFPA 1971-8.6 (2018)

CASE MATERIAL

- 6061-T6 aluminum
- Serialized

LUMENS/RUNTIME**SPOTLIGHT**

- HIGH: 360L, 3.5 hrs. runtime
- MEDIUM: 180L, 10 hrs. runtime
- LOW: 25L, 30 hrs. runtime

CANDELA

- HIGH: 11,928
- MEDIUM: 6,544
- LOW: 472

BEAM DISTANCE**SPOTLIGHT**

- HIGH: 218m
- MEDIUM: 161m
- LOW: 43m

WATER RATING

- IP-67 (dustproof, waterproof)

DROP RATING

- 2 meters

DIMENSIONS

- LENGTH: 3.2 in (81mm)
- WIDTH: 1.4 in (36mm)
- DEPTH: 3.2 in (81mm)
- BEZEL DIAMETER: 1.1 in (28mm)
- WEIGHT: 7.2 oz (204g)

BATTERY

- 2 CR123 batteries (included)

WARRANTY

- Limited lifetime warranty

WHAT'S INCLUDED

- Helmet Light
- 2 CR123 batteries
- Allen wrench

FL 1 STANDARD	HIGH	MEDIUM	LOW
	360 LUMENS	180 LUMENS	25 LUMENS
	4h 30min	6h 30min	30h
	218m	161m	43m
	11928cd	6544cd	472cd
			

US Patent 9,713,217

Bayco Products, Inc. XPP-5465
640 S. Sanden Blvd., Wylie, TX 75098



ID 5012927
INTRINSICALLY SAFE
SECURITE INTRINSEQUE



CLASS I DIV 2 GRPS A-D T3
CLASS II & III DIV 2 GRPS F-G T135°C
CLASS I ZONE 2 GROUP IIC T3
-20°C ≤ Tamb ≤ +40°C
(2) CR-123 3.0V/Cell



WARNING: Risk of ignition - Do not open in a hazardous area.
AVERTISSEMENT: Ne pas ouvrir dans une zone dangereuse.
WARNING: Risk of ignition - Do not change batteries in a hazardous area. AVERTISSEMENT: Danger d'inflammation - Ne changez pas les piles dans une zone dangereuse.

SEE INSTRUCTION MANUAL
VOIR MANUEL

MFD: MM/YY

