



Chemical protection

# ULTRANITRIL 480

Prolonged contact (or immersion) | short wear

## Ultra-long chemical protection



CHEMICAL PROTECTION  
**TYPE A**

EN388



4102X

EN ISO 374-1



TYPE A  
AJKOPT

EN ISO 374-5



ISO 18889

CAT.CATEGORY 3



0334

DEXTERITY

EN 420:  
5/5



### SPECIFIC ADVANTAGES



#### Durability

- Longer service life: excellent mechanical resistance (abrasion, perforation)



#### Productivity

- Good grip on slippery objects, due to the embossed texture



#### Skin protection

- Excellent protection during intensive handling of high-risk chemical products



#### Guaranteed quality

- Silicone free to prevent traces, defects on metal sheet and glass prior to painting

### INDUSTRIES

- Automotive/mechanical industry
- Chemical industry
- Other industries
- Agriculture sector

### APPLICATIONS

- Application of pesticides
- Cleaning of printing-press rollers
- Maintenance
- Timber treatment and finishing
- Treating/degreasing metals with aggressive solvents
- Handling drums of chemical products
- Spray mixtures preparation
- Tank filling
- Application & spreading of pesticides
- Pesticides waste management



Chemical protection

# ULTRANITRIL 480

Prolonged contact (or immersion) | short wear

## LEGENDS

EN388	MECHANICAL HAZARDS
	PERFORMANCE LEVELS (X = NOT TESTED)
4 1 0 2 X	
0-4 0-5 0-4 0-4 A-F P	
	Impact protection (optional)
	Cut resistance according to ISO 13997
	Puncture resistance
	Tear resistance
	Blade cut resistance
	Abrasion resistance

EN ISO 374-1	CHEMICAL RISKS
	A: Methanol
	J: n-Heptane
	K: Sodium hydroxide 40%
	O: Ammonia 25%
	P: Hydrogen peroxide 30%
	T: Formaldehyde 37%
TYPE A	

	PROTECTION FROM PESTICIDES
G2	G2: Diluted & concentrated pesticides / Mechanical risk

ISO 18889

EN ISO 374-5	MICRO-ORGANISMS
	Protection against bacteria and fungi



FOOD CONTACT  
French decree of 05/08/2020

## PRODUCT DETAILS

Interior finish	Chlorinated
Exterior finish	Embossed texture
Material	Nitrile
Cuff characteristic	Straight cuff
Colour.s	Green
Length (cm)	46
Thickness (mm)	0.55
European sizes	7 8 9 10 11

## LOGISTIC DETAILS

Packaging	1 pair/bag 12 pairs/carton
-----------	-------------------------------

## LEGISLATION

- This product is not classified hazardous according to the regulation (EC) n°1272/2008 of the European Parliament and of the Council.
- This product does not contain more than 0.1 % of substance of very high concern (SVHC) or any substance included in the annex XVII of the regulation n° 1907/2006 of the European Parliament and of the Council (REACH).
- UE type certificate or CE type examination certificate: 0075/014/16206/18/1069
- Issued by the notified body nr: 0075 CTC - 4, rue Hermann Frenkel - 69367 Lyon Cedex 07- FRANCE
- Quality assurance certificat: 0334 - Asqual 14 rue des Reculettes -75013 Paris - France