



Chemical protection

# ULTRANITRIL 492

Frequent contact | intermittent wear



CHEMICAL PROTECTION  
**TYPE A**



EN388  
3101X



EN ISO 374-1  
TYPE A  
AJKOPT



EN ISO 374-5  
VIRUS



ISO 18889



CAT. CATEGORY 3

DEXTERITY

EN 420:  
5/5

Good mechanical resistance and long-lasting chemical protection

## SPECIFIC ADVANTAGES

### Comfort

- Dexterity and comfort, due to the anatomical shape and the quality of the flock-lining

### Durability

- Longer service life: excellent mechanical resistance (abrasion, perforation)

### Guaranteed quality

- Silicone free to prevent traces, defects on metal sheet and glass prior to painting

### Additional benefits

- Available in vending machine packaging

## INDUSTRIES

- Automotive/mechanical industry
- Local Authorities (Cleaning)
- Local Authorities (Parks and Public Spaces)
- Construction Industry (Masons / Plasterers)
- Construction Industry (Carpenters/Joiners)
- Agriculture sector

## APPLICATIONS

- Handling aggressive chemical products
- Machining parts using cutting oil
- Treating/degreasing metals with solvents
- Plant Treatment Products
- Handling oils, solvents, detergents
- Preparing coatings, varnishes
- Handling PVC-based glues
- Spray mixtures preparation
- Pesticides handling
- Tank filling



Chemical protection

# ULTRANITRIL 492

Frequent contact | intermittent wear

## ( LEGENDS )

EN388

**MECHANICAL HAZARDS**

PERFORMANCE LEVELS (X = NOT TESTED)					
3	1	0	1	X	
0-4	0-5	0-4	0-4	A-F	P
					Impact protection (optional)
					Cut resistance according to ISO 13997
					Puncture resistance
					Tear resistance
					Blade cut resistance
					Abrasion resistance

EN ISO 374-1

**CHEMICAL RISKS**

A: Methanol  
 J: n-Heptane  
 K: Sodium hydroxide 40%  
 O: Ammonia 25%  
 P: Hydrogen peroxide 30%  
 T: Formaldehyde 37%

TYPE A

**PROTECTION FROM PESTICIDES**

G2: Diluted &amp; concentrated pesticides / Mechanical risk

ISO 18889

**MICRO-ORGANISMS**

Protection against bacteria, fungi and virus

VIRUS

## ( PRODUCT DETAILS )

Interior finish	Flocked
Exterior finish	Embossed texture
Material	Nitrile
Cuff characteristic	Straight cuff
Colours	Green
Length (cm)	32
Thickness (mm)	0.38
European sizes	6 7 8 9 10 11
Surface resistance according to EN1149-1 (Value in palm area at 25% relative humidity)	6.4E+10 Ω
Vertical resistance according to EN1149-2 (Value in palm area at 25% relative humidity)	5.8E+9 Ω

## ( LOGISTIC DETAILS )

**Packaging**

1 pair/bag  
 10 pairs/bag  
 100 pairs/carton

## ( LEGISLATION )

- This product is not classified hazardous according to the regulation (EC) n°1272/2008 of the European Parliament and of the Council.
- This product does not contain more than 0.1 % of substance of very high concern (SVHC) or any substance included in the annex XVII of the regulation n° 1907/2006 of the European Parliament and of the Council (REACH).
- UE type certificate or CE type examination certificate: 0075/014/162/08/18/1631
- Issued by the notified body nr: 0075 CTC - 4, rue Hermann Frenkel - 69367 Lyon Cedex 07- FRANCE
- Quality assurance certificate: 0334 - Asqual 14 rue des Reculettes -75013 Paris - France